

LUXT@UCH
A TOUCH OF ELEGANCE

LUXT@UCH

LUXT@UCH
A TOUCH OF ELEGANCE

INFUSING LIFE WITH COLOR!

Our Colors are Designed to
Evoke Emotion
& Create Spaces that Feel Alive



A TOUCH OF ELEGANCE



Incredible Story of Colors



A LOOK INSIDE

Elevate your spaces with our premium laminates. We committed to delivering exceptional quality, style and durability. Our products transform homes and businesses into stunning environments.

We create surfaces that are not only visually appealing but also highly functional. Our commitment to quality ensures that every laminate we produce exceeds expectations.

We are dedicated to creating beautiful and sustainable spaces. Our laminates are crafted using eco-friendly materials and processes, without compromising on style or performance.



UREA FREE
PRODUCT



CARDANOL
FREE



ENOUGH
THICKNESS



100%
PHENOLIC



BEST
QUALITY




FEATURES

Elegance that Endures



Easy to
Clean




Anti
Bacterial




Scratch
Resistant



Dimensional
Stability



100%
Phenolic



Fade
Resistant



Stain
Resistant



Heat
Resistant

NATURE'S PALETTE

Inspired by The Nature's



LUXT@UCH
A TOUCH OF ELEGANCE



TRANQUIL RETREAT

Create a Serene and Peaceful Environment

LUXT@UCH
A TOUCH OF ELEGANCE



SMT 771

Muted Mink




SMT 770

Dove Gray

ECLECTIC
ELEGANCE

Encourage Self-Expression and Creativity


LUXT@UCH
A TOUCH OF ELEGANCE



762

SMT 762

Mist Haven



763

SMT 763

Serene Slate



WELCOMING ATMOSPHERE

Infuse your space with the
Inviting warmth of rich



UREA FREE
PRODUCT



CARDANOL
FREE



100%
PHENOLIC

LUXT@UCH
A TOUCH OF ELEGANCE

767

SMT **767**

Whispering Almond

201

SMT **201**

Silver Haze



ETHEREAL LIGHT

Capturing the Essence of
Light and Airiness

229

SMT **229**

Frosted Pearl



ARTISTIC EXPRESSION


Our Rich and Diverse Color Collection

LUXT@UCH
A TOUCH OF ELEGANCE



SMT 766

Steel Whisper



SMT 769

Urban Fog



RUSTIC REVIVAL

Colors of the Countryside



743

SMT 743 Slate Veil

768

SMT 768 Shadow Silk

708

SMT 708 Moonlit Ash

TIMELESS ELEGANCE

Classic Colors for Modern Living

LUXURY AND
SOPHISTICATION

Perfect for making a statement.



UREA FREE
PRODUCT



CARDANOL
FREE



100%
PHENOLIC

LUXT@UCH
A TOUCH OF ELEGANCE

758

SMT 758

Petal Cream

765

SMT 765

Ivory Whisper



WHISPERING
PASTELS

Soft Tones, Strong Impact


755

SMT 755

Sand Dune


MIDNIGHT
MYSTIQUE

Refined Colors for a Sophisticated Interior



SMT 761

Quartz Mist



SMT 747

Pearl Blush



UREA FREE
PRODUCT

CARDANOL
FREE

100%
PHENOLIC



MODERN &
MINIMALISM

Our Modern Minimalist Palette

746

SMT **746**

Peach Whip

VINTAGE REVIVAL

Where Every Color Holds a Piece of History

LUXT@UCH

A TOUCH OF ELEGANCE

764

SMT **764**

Olive Henna

754

SMT **754**

Wheat Husk

15
16



MYSTICAL TWILIGHT

The Beauty of Both Sunrise and Sunset

LUXT@UCH
A TOUCH OF ELEGANCE

759

SMT 759

Ballet Beige

760

SMT 760

Rose Meringue

745

SMT 745

Skyline Hue

748

SMT 748

Ocean Mist


ARTISTIC EXPRESSION

Our Rich and Diverse Color Collection



ENCHANTED TONES

Our Mystical Color Collection




701

60 x 175mm

SMT 701

Slate Frost



702

SMT 702

Oatmeal Cream

URBAN JUNGLE

Our Dynamic and Lush Color Selection



UREA FREE
PRODUCT




CARDANOL
FREE



100%
PHENOLIC

LUXT@UCH
A TOUCH OF ELEGANCE



705

SMT 705


Indigo Drift



ARTISTIC EXPRESSION


Our Rich and Diverse Color Collection

LUXT@UCH
A TOUCH OF ELEGANCE



SMT **704**

Ink Storm



SMT **724**

Granite Smoke

TIMELESS AND VERSATILE

Achieve a balanced and classic look with Neutral shades, provide a foundation of Elegance and flexibility.



INDEX

NO.	DESIGN NO.	FINISH	PAGE NO.
1	771	SMT	02
2	770	SMT	02
3	762	SMT	03
4	763	SMT	03
5	767	SMT	05
6	201	SMT	05
7	229	SMT	06
8	766	SMT	08
9	769	SMT	08
10	743	SMT	09
11	768	SMT	10
12	708	SMT	10
13	758	SMT	11
14	765	SMT	11
15	755	SMT	12

NO.	DESIGN NO.	FINISH	PAGE NO.
16	761	SMT	13
17	747	SMT	13
18	746	SMT	15
19	764	SMT	16
20	754	SMT	16
21	759	SMT	18
22	760	SMT	18
23	745	SMT	19
24	748	SMT	19
25	701	SMT	21
26	702	SMT	21
27	705	SMT	22
28	704	SMT	24
29	724	SMT	24

Laying Instructions for HPL Laminate Sheets

Before use ensures that the surface or plywood and laminates is Clean, Dry, Leveled and free of Oil, Excess moisture or other contaminants, such as dust, synthetic particles, etc. Only use white PVA Adhesive to stick the sheet. Apply Double Layer of Adhesive on Edge (Minimum 3-4 Inch) of Both The Surfaces. The adhesive should always be stirred before use. Sufficient adhesive should be applied on both of the surface to be bonded. Don't add water into the adhesive, it makes the bonding weak. Once adhesive applied is trickily in nature (Usually requires 5-10 minutes, depending on atmospheric conditions), the laminate should be placed on the surface, accurately aligned. Sufficient bonding procedure to ensure intimate contact necessary for an adequate bond should be applied over the entire area using as much as procedure as possible as possible without damaging the assembly.

Pinch rollers (Rotary Press) and heavy weighted rollers are ideal; Hand rolling should be done from the centre to the edges to ensure the removal of air bubbles. The edges should be rolled twice. For Satisfactory bonding, the area in question should be kept under pressure fir a period of 12-18 hours (Depending on atmospheric conditions). In rainy season or when humidity is too high, moisture may condense on the surface during drying (Know as "Blushing") and will prevent an acceptable. Hot Spray or Forced air drying may be used to help prevent this condition.

- It is recommended that the maximum sheet size used for vertical field application be limited to 610x2440 mm (2x8 Ft.).
- When laminate is pasted vertically, Maintain uniform pressure on all sides till adhesive is dried.
- To avoid stress cracking, avoid making cut out having sharp corners and rough edges.
- A gap of minimum 2 mm should be maintained between two laminates while pasting side by side.
- Due to transportation limitations laid the laminate sheet on flat surface in between 2 plywood sheets for minimum 48 Hrs.